



C-EW Adjustable Elbow-Fitting with Cone

24° Swivel (DIN EN ISO 8434-1) /
24° Tube Connection (DIN EN ISO 8434-1)



C-EW-R-WD



Series	PN [bar]		ØD1 [mm]	ØD3 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L4 [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/100
	C	CF										
L	315	500	6	4	19	12.0	26.0	27	12	14	C-EW 06 L OMD	2.9
			8	6	21	14.0	27.5	29	12	17	C-EW 08 L OMD	4.1
			10	8	22	15.0	29.0	30	14	19	C-EW 10 L OMD	5.3
	315	400	12	10	24	17.0	29.5	32	17	22	C-EW 12 L OMD	7.1
			15	12	28	21.0	32.5	36	19	27	C-EW 15 L OMD	12.8
			18	15	31	23.5	35.5	40	24	32	C-EW 18 L OMD	17.2
	160	250	22	19	35	27.5	38.5	44	27	36	C-EW 22 L OMD	23.4
			28	24	38	30.5	41.5	47	36	41	C-EW 28 L OMD	33.4
			35	30	45	34.5	51.0	56	41	50	C-EW 35 L OMD	51.7
			42	36	51	40.0	56.0	63	50	60	C-EW 42 L OMD	78.3
S	630	800	6	4	23	16.0	27.0	31	12	17	C-EW 06 S OMD	4.6
			8	5	24	17.0	27.5	32	14	19	C-EW 08 S OMD	6.1
			10	7	25	17.5	30.0	34	17	22	C-EW 10 S OMD	8.1
	630	630	12	8	29	21.5	31.0	38	17	24	C-EW 12 S OMD	10.4
			14	10	30	22.0	35.0	40	19	27	C-EW 14 S OMD	14.6
	400	630	16	12	33	24.5	36.5	43	24	30	C-EW 16 S OMD	18.9
			20	16	37	26.5	44.5	48	27	36	C-EW 20 S OMD	29.0
	400	400	25	20	42	30.0	50.0	54	36	46	C-EW 25 S OMD	53.6
			30	25	49	35.5	55.0	62	41	50	C-EW 30 S OMD	70.5
			38	32	57	41.0	63.0	72	50	60	C-EW 38 S OMD	107.4
	250	400	38	32	57	41.0	63.0	72	50	60	C-EW 38 S OMD	107.4

*Replace the character "C" with "CF" when you require steel!
C = Stainless Steel, 1.4571 (Seal FKM) CF = Galvanized Steel Cr(VI)-free (Seal NBR)