





C-GE-R-KEG

Male Stud Connector

Male BSPP Stud Connector - Tapered (DIN 3852-2 Type C) /
24° Tube Connection (DIN EN ISO 8434-1)



C-GE-M-KEG
(LL)



Series	PN [bar]		ØD ₁ [mm]	T	ØD ₃ [mm]	L ₁ [mm]	L ₂ [mm]	L ₃ [mm]	L ₄ [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/ 100
	C	CF											
LL	100	100	4	R1/8KEG	3.0	20	16.0	8	26	11	10	C-GE 04 LLR KEG X	0.8
			6	R1/8KEG	4.5	20	14.5	8	26	11	12	C-GE 06 LLR KEG X	1.0
			8	R1/8KEG	6.0	22	16.5	8	28	12	14	C-GE 08 LLR KEG X	1.0
			8	R1/4KEG	6.0	26	20.5	12	32	14	14	C-GE 08 LLR 1/4 KEG X	2.0
			10	R1/4KEG	8.0	26	20.5	12	32	14	17	C-GE 10 LLR KEG X	2.4
			12	R1/4KEG	8.0	26	20.0	12	32	17	19	C-GE 12 LLR KEG X	5.3
			12	R3/8KEG	10.0	26	20.0	12	32	17	19	C-GE 12 LLR 3/8 KEG X	3.3
L	315	315	6	R1/8KEG	4.0	22	15.0	8	30	12	14	C-GE 06 LR 1/8 KEG X	1.1
			6	R1/4KEG	4.0	27	20.0	12	35	17	14	C-GE 06 LR 1/4 KEG X	2.0
			8	R1/8KEG	4.0	23	16.0	8	31	17	17	C-GE 08 LR 1/8 KEG X	1.5
			8	R1/4KEG	6.0	27	20.0	12	35	17	17	C-GE 08 LR 1/4 KEG X	2.0
			10	R1/4KEG	7.0	28	21.0	12	36	17	19	C-GE 10 LR 1/4 KEG X	2.4
			12	R1/4KEG	7.0	29	22.0	12	37	19	22	C-GE 12 LR 1/4 KEG X	3.0
			12	R3/8KEG	9.0	29	22.0	12	37	19	22	C-GE 12 LR 3/8 KEG X	3.4
			12	R1/2KEG	10.0	31	24.0	14	39	24	22	C-GE 12 LR 1/2 KEG X	4.9
			15	R3/8KEG	9.0	30	23.0	12	38	24	27	C-GE 15 LR 3/8 KEG X	4.8
			15	R1/2KEG	11.0	32	25.0	14	40	24	27	C-GE 15 LR 1/2 KEG X	5.4
			18	R1/2KEG	14.0	33	25.5	14	42	27	32	C-GE 18 LR 1/2 KEG X	6.4
	160	160	22	R3/4KEG	17.0	37	29.5	16	46	32	36	C-GE 22 LR 3/4 KEG X	9.8
			28	R1KEG	23.0	40	32.5	18	49	41	41	C-GE 28 LR 1 KEG X	15.4
			35	R1 1/4KEG	30.0	45	34.5	20	56	46	50	C-GE 35 LR 1 1/4 KEG X	23.5
			42	R1 1/2KEG	36.0	49	38.0	22	61	55	60	C-GE 42 LR 1 1/2 KEG X	33.4

*Replace the character "C" with "CF" when you require steel!

C = Stainless Steel, 1.4571 CF = Galvanized Steel Cr(VI)-free