





C-KOVO SWIVEL REDUCER

24° Swivel (DIN EN ISO 8434-1) /
24° Tube Connection (DIN EN ISO 8434-1)



C-KOVO



Series	PN [bar]		ØD ₁ [mm]	ØD ₂ [mm]	ØD ₃ [mm]	L ₁ [mm]	L ₂ [mm]	L ₃ [mm]	S1 [mm]	S2 [mm]	S3 [mm]	Ordering Code*	kg/100
	C	CF											
L	315	500	6	8	2.5	31.5	24.5	39.5	14	14	17	C-KOVO 06/08 L OMD	2.6
L/S	315	500	6	8	2.5	33.5	26.5	41.5	17	14	19	C-KOVO 06 L/08 S OMD	3.5
L	315	500	6	10	2.5	32.5	25.5	40.5	17	14	19	C-KOVO 06/10 L OMD	3.0
L/S	315	500	6	10	2.5	34.5	27.0	43.5	19	14	22	C-KOVO 06 L/10 S OMD	4.1
L	315	400	6	12	2.5	33.5	26.5	41.5	19	14	22	C-KOVO 06/12 L OMD	3.6
L/S	315	500	6	12	2.5	34.5	27.0	43.5	22	14	24	C-KOVO 06 L/12 S OMD	4.9
	315	500	6	14	2.5	36.5	28.5	46.5	24	14	27	C-KOVO 06 L/14 S OMD	5.8
L	315	400	6	15	2.5	34.5	27.5	42.5	24	14	27	C-KOVO 06/15 L OMD	5.2
	315	500	8	10	4.0	32.5	25.5	40.5	17	17	19	C-KOVO 08/10 L OMD	3.8
L/S	315	500	8	10	4.0	34.5	27.0	43.5	19	17	22	C-KOVO 08 L/10 S OMD	4.8
L	315	400	8	12	4.0	33.5	26.5	41.5	19	17	22	C-KOVO 08/12 L OMD	4.3
L/S	315	500	8	12	4.0	34.5	27.0	43.5	22	17	24	C-KOVO 08 L/12 S OMD	5.6
	315	500	8	14	4.0	36.5	28.5	46.5	24	17	27	C-KOVO 08 L/14 S OMD	6.6
L	315	400	8	15	4.0	34.5	27.5	42.5	24	17	27	C-KOVO 08/15 L OMD	5.8
L/S	315	500	10	10	6.0	34.0	26.5	43.0	19	19	22	C-KOVO 10 L/10 S OMD	5.2
L	315	400	10	12	6.0	33.0	26.0	41.0	19	19	22	C-KOVO 10/12 L OMD	4.6
L/S	315	500	10	12	6.0	34.0	26.5	43.0	22	19	24	C-KOVO 10 L/12 S OMD	5.8
	315	500	10	14	6.0	36.0	28.0	46.0	24	19	27	C-KOVO 10 L/14 S OMD	6.7
L	315	400	10	15	6.0	34.0	27.0	42.0	24	19	27	C-KOVO 10/15 L OMD	6.0
L/S	315	500	10	16	6.0	37.0	28.5	47.0	27	19	30	C-KOVO 10 L/16 S OMD	7.9
L	315	400	10	18	6.0	35.0	27.5	44.0	27	19	32	C-KOVO 10/18 L OMD	7.5
L/S	315	400	12	12	8.0	34.0	26.5	43.0	22	22	24	C-KOVO 12 L/12 S OMD	6.7
	315	400	12	14	8.0	36.0	28.0	46.0	24	22	27	C-KOVO 12 L/14 S OMD	7.6
L	315	400	12	15	8.0	34.0	27.0	42.0	24	22	27	C-KOVO 12/15 L OMD	6.9
L/S	315	400	12	16	8.0	37.0	28.5	47.0	27	22	30	C-KOVO 12 L/16 S OMD	8.8
L	315	400	12	18	8.0	35.0	27.5	44.0	27	22	32	C-KOVO 12/18 L OMD	8.3

*Replace the character "C" with "CF" when you require steel!
C = Stainless Steel, 1.4571 (Seal FKM) CF = Galvanized Steel Cr(VI)-free (Seal NBR)