

# Gietijzeren aanboorzadels ANB

T-verbinding met binnenschroefdraad



**Voor stalen buis:** DIN EN 10255 (vroeger DIN 2440/2441), DIN 2442 en DIN 2448/DIN 2458 serie 1, ISO 65

- **Middelen:** Water
- **Temperaturen:** drinkwater: tot 25 °C;  
verwarmingswater: tot 90 °C

**17,2 mm–114,3 mm:**

- **Druktrappen:** Water PN 16



DN	Buisbuiten-Ø [mm] x Aansluit- schroefdraad	Art.-nr.
10	17,2 x 3/8"	01.261.28.0000
15	21,3 x 1/2"	01.261.28.0101
20	26,9 x 1/2"	01.261.28.0201
25	33,7 x 1/2"	01.261.28.0301
25	33,7 x 3/4"	01.261.28.0302
32	42,4 x 3/4"	01.261.28.0402
40	48,3 x 3/4"	01.261.28.0502
50	60,3 x 1"	01.261.28.0603
65	76,1 x 1"	01.261.28.0703
65	76,1 x 1 1/4"	01.261.28.0704
65	76,1 x 1 1/2"	01.261.28.0705
80	88,9 x 1"	01.261.28.0803
80	88,9 x 1 1/4"	01.261.28.0804
80	88,9 x 1 1/2"	01.261.28.0805
80	88,9 x 2"	01.261.28.0806
100	114,3 x 1"	01.261.28.0903
100	114,3 x 1 1/4"	01.261.28.0904
100	114,3 x 1 1/2"	01.261.28.0905
100	114,3 x 2"	01.261.28.0906

## Afmetingen en gewichten

DN	Aansluit- schroefdraad Rp ISO 7/1	Buis- buiten-Ø [mm]	Gewicht [kg]	Constructie- lengte -A [mm]	-B [mm]	-C [mm]	-D [mm]	-E [mm]
10	3/8"	17,2	0,2	70	28	53	36	22
15	1/2"	21,3	0,3	70	33	60	50	31
20	1/2"	26,9	0,4	70	40	70	55	32
25	1/2"	33,7	0,5	70	46	74	61	37
	3/4"		0,5	70	46	74	61	37
32	3/4"	42,4	0,6	80	57	86	75	45
40	3/4"	48,3	1,0	100	66	94	85	48
50	1"	60,3	1,2	100	80	109	100	60
65	1"	76,1	2,0	100	100	140	115	65
	1 1/4"		2,0	100	100	140	115	65
	1 1/2"		2,0	100	100	140	115	65
80	1"	88,9	2,4	100	115	150	131	75
	1 1/4"		2,4	100	115	150	131	75
	1 1/2"		2,4	100	115	150	131	75
	2"		3,2	135	115	150	136	75
100	1"	114,3	2,9	100	140	187	160	90
	1 1/4"		3,3	100	140	187	160	90
	1 1/2"		3,3	100	140	187	160	90
	2"		4,4	135	140	187	165	90

## Aanboorzadel voor stalen buis

17,2 mm–114,3 mm

