

Gietijzeren reparatiezadels DS

Om gaten, scheuren, poreuze plekken af te dichten

Voor stalen buis: DIN EN 10255 (vroeger DIN 2440/2441), DIN 2442 en DIN 2448/DIN 2458 serie 1, ISO 65

- **Middelen:** Water
- **Temperaturen:** drinkwater: tot 25 °C;
verwarmingswater: tot 90 °C

17,2 mm – 114,3 mm:

- **Druktrappen:** Water PN 16



DN	Buisbuiten-Ø	Art.-nr.
	[mm]	
10	17,2 (3/8")	01.260.28.00
15	21,3 (1/2")	01.252.28.01
20	26,9 (3/4")	01.252.28.02
25	33,7 (1")	01.252.28.03
32	42,4 (1 1/4")	01.252.28.04
40	48,3 (1 1/2")	01.252.28.05
50	60,3 (2")	01.252.28.06
65	76,1 (2 1/2")	01.252.28.07
80	88,9 (3")	01.252.28.08
100	114,3 (4")	01.252.28.09

Afmetingen en gewichten

DN	Buisbuiten-Ø [mm]	Gewicht [kg]	Constructie- lengte ~A [mm]	~B [mm]	~C [mm]
10	17,2	0,3	70	28	53
15	21,3	1,1	134	45	84
20	26,9	1,1	134	50	88
25	33,7	1,3	134	57	98
32	42,4	1,5	134	70	105
40	48,3	1,6	134	75	112
50	60,3	1,8	134	90	122
65	76,1	2,2	134	105	139
80	88,9	3,0	134	115	155
100	114,3	3,0	134	140	194

Reparatiezadel voor stalen buis

17,2 mm – 114,3 mm

